



SLIPKOTE® Specialty Lubricants

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

Eastern Region Office:

8300 Corporate Park Drive, Macedonia, Ohio 44056
(330) 425-2567 • FAX (330) 425-9637
(800) 238-5823 • www.speclubes.com

Western Region Office:

1580 Industrial Avenue, Norco, California 92860
(951) 340-4000 • FAX (951) 340-4011
(800) 4-HUSKEY • www.huskey.com

MATERIAL SAFETY DATA SHEET

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: SLIPKOTE Air Tool Oil
PRODUCT CODE: 58100
REVISION DATE: 02/15/12

MANUFACTURER: SPECIALTY LUBRICANTS CORPORATION
8300 Corporate Park Drive
Macedonia, OH 44056 USA
(P): 1-800-238-5823
(F): 1-330-425-9637

EMERGENCY PHONE: 800-424-9300 (24HR)
CHEMTREC PHONE: 800-424-9300 (24HR)

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

	CAS NO.	%
HYDROTREATED HEAVY PARAFFINIC DISTILLATES	64742-54-7	99
ZINC DIALKYL DITHIOPHOSPHATE ADDITIVE	68649-42-3	<1

* This product is not considered a "Hazardous Material" in normal use as defined in OSHA 29 CFR 1910.1200

SECTION 3: PHYSICAL DATA

APPEARANCE:	ASTM 1.0 Liquid	VISCOSITY AT 100°F, SUS:	148.2
SPECIFIC GRAVITY:	31.4	VISCOSITY AT 210°F, SUS:	43.8
BOILING POINT, °F:	N/A	ODOR:	Very mild
pH:	N/A	FLASH POINT, °F:	435
WATER SOLUBILITY:	No	POUR POINT, °F:	-25
VAPOR PRESSURE (MM HG 20C):	N/A		

SECTION 4: FIRE AND EXPLOSION

FLASH POINT: 345° F.

FLAMMABILITY (Explosive) LIMITS (% by volume in air): **UPPER:** 0.6% **LOWER:** 7.0%

EXTINGUISHING MEDIA: Dry chemical, foam, carbon dioxide, water spray.

SPECIAL FIRE FIGHTING PROCEDURES: Use water spray to cool fire exposed surfaces and protect personnel.

UNUSUAL FIRE AND EXPLOSION HAZARDS: None.

SECTION 5: HEALTH HAZARDS DATA

THRESHOLD LIMIT VALUE: Oil mist 5mg/m³
EFFECTS OF OVEREXPOSURE: Low order of toxicity and irritancy.
EMERGENCY AND FIRST AID PROCEDURES: If liquid contacts eyes, flush promptly with water until any irritation subsides.

SECTION 6: REACTIVITY DATA

STABILITY: Stable.
INCOMPATIBILITY: Avoid contact with strong oxidizers.
CONDITIONS TO AVOID: Extreme heat.
HAZARDOUS POLYMERIZATION: Will not occur.
HAZARDOUS DECOMPOSITION: Carbon monoxide.

SECTION 7: SPILL OR LEAK PROCEDURE

STEPS TO BE TAKEN IN CASE OF LEAK OR SPILL: Shut off source if possible to do so without hazard. Advise police if substance has entered a water course or sewer.
WASTE DISPOSAL METHOD: Contain spilled liquid with sand or floor-dri. Incinerate in an approved manner conforming to local disposal regulations.

SECTION 8: SPECIAL PROTECTION INFORMATION

VENTILATION: Usually not needed in open unconfined area.
RESPIRATORY PROTECTION: Usually not needed.
EYE PROTECTION: Safety glasses.
PROTECTIVE GLOVES: Oil/chemical resistant gloves to minimize skin contact.
OTHER PROTECTION: Usually not needed.

SECTION 9: SPECIAL PRECAUTIONS

HANDLING AND STORAGE: Keep container closed when not in use. Keep away from heat and open flames.
OTHER PRECAUTIONS: Avoid eye contact. Avoid breathing oil mists.

SECTION 10: ADDITIONAL INFORMATION

	<u>Health</u>	<u>Fire</u>	<u>Reactivity</u>
HMIS CODE:	1	1	0
NFPA RATINGS:	0	1	0

The above information is based on the data of which we are aware and believed to be correct as of the date hereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modification of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his/her own determination of the suitability of the material for his/her particular purpose.

N/D	Not Determined	N/A	Not Applicable	TLV	Threshold Limit Value (ACGIH)
<	Less Than	>	Greater Than	PEL	Permissible Exposure Limit (OSHA)